Arvados - Bug #16566

[cli] can't create a token when using a token created with create_superuser_token.rb

06/26/2020 12:50 AM - Ward Vandewege

Status:	New	**Start date:**	
Priority:	Normal	**Due date:**	
Assigned To:		**% Done:**	0%
Category:		**Estimated time:**	0.00 hour
Target version:			

Description

Error:

```
Error: #<ActiveRecord::StatementInvalid: PG::NotNullViolation: ERROR:  null value in column "api_client_id" violates not-null constraint
```

Steps to reproduce:

1. Create a system root token with create_superuser_token.rb. This is a v1 token.
2. load it in ARVADOS_API_TOKEN
3. try to create a token, e.g. with the instructions from the `Create scoped token` section on the `Set up a shell node` page:

```
$ arv api_client_authorization create --api-client-authorization '{"scopes":["GET /arvados/v1/virtual_machines/zzzzz-2x53u-zzzzzzzzzzzzzzz/logins"]}'
```

The system root token isn't associated with a client.

Related issues:

Related to Arvados - Bug #16613: System Root Token cannot create tokens - nul...	**Resolved**	**08/25/2020**

History

#1 - 06/26/2020 12:52 AM - Ward Vandewege

- Description updated

#2 - 07/17/2020 03:34 PM - Ward Vandewege

- Related to Bug #16613: System Root Token cannot create tokens - null value in column "api_client_id" added

#3 - 07/06/2021 09:08 PM - Peter Amstutz

- Target version deleted (To Be Groomed)